



Catalog

GoldNova Machinery Co.,Ltd

**GoldNova
Tractor**





关于我们/About us

金诺瓦公司秉承“诚信、创新、激情、合作”

为核心价值观，致力于研发农民买着放心、用着舒心、可靠性高的农机产品，
为提升现代农机化水平贡献一份力量！

GoldNova Company adheres to the core values of "integrity, innovation, passion, and cooperation" and is committed to developing agricultural machinery products that farmers can buy with confidence, use comfortably, and have high reliability, and contribute to improving the level of modern agricultural mechanization!



诚信
honesty



创新
innovate



激情
passion



合作
cooperate



XD系列-轮式拖拉机
XD series-wheeled tractor

技术特点/ Technical features

- 1、动力优越，匹配国内玉柴、潍柴、云内、名牌电控四缸发动机，动力性能优越，节能环保，经济高效、作业高效。
- 2、变速箱12+12同步器梭式换挡，前进、后退可快速切换：档位速度匹配多，可根据不同农具、不同土壤选择最佳的作业速度。
- 3、先进底盘制造技术，加大半轴，性能安全可靠。
- 4、豪华驾驶室，空调暖风、多媒体影像选配，独家配备220L超大型油箱，加强型悬挂系统。
- 5、采用独立的液压供油系统，并选装双路及多路液压输出满足多样化机具作业。
- 6、12寸双作用离合器、换挡动力输出链接更方便。

- 1、Excellent power. It is matched with domestic well - known brand electronically - controlled four - cylinder engines such as Yuchai, Weichai, and Yunnei. It has excellent power performance, is energy - saving, environmentally friendly, cost - effective, and highly efficient in operation.
- 2、The gearbox has a 12+12 synchronizer shuttle shift, which allows for quick forward and backward switching. There are multiple gear - speed combinations, enabling the selection of the optimal operating speed according to different agricultural tools and soil conditions.
- 3、With advanced chassis manufacturing technology and enlarged half - axles, it has safe and reliable performance.
- 4、The luxurious cab offers optional air - conditioning, heating, and multimedia imaging systems. It is exclusively equipped with a 220L super - large fuel tank and a reinforced suspension system.
- 6、It adopts an independent hydraulic oil supply system, and dual - circuit and multi - circuit hydraulic outputs can be optionally installed to meet the needs of diversified machinery operations.
- 6、The 12 - inch double - acting clutch makes the shift power output connection more convenient.

机 型/ models		1004-D	1204-D
整机驱动型式 Whole machine drive type	/	四驱/ Four-wheel drive	四驱/ Four-wheel drive
整机外廓尺寸(长*宽*高及部位) Overall dimensions of the whole machine (length * width * height and position)	mm	4590*2050*2990 (安全架/Safety frame) 4850*2050*2900 (驾驶室/cab)	4590*2050*2990 (安全架/Safety frame) 4850*2050*2900 (驾驶室/cab)
轴距或履带接地长 Wheelbase or track grounding length	mm	2250	2250
轮距(前轮/后轮)或轨距 Track (front/rear wheels) or gauge	mm	1300-1800/1300-1800	1300-1800/1300-1800
挡位数 (前进/倒退) Number of gears (forward/backward)	/	12+12	12+12
发动机厂家 Engine manufacturer	/	玉柴/Yuchai	玉柴/Yuchai
发动机型号 Engine model	/	YCF39120-T482	39140-T482
发动机标定功率 Engine calibration power	kw	73.5	88.2
轮胎型号(前轮/后轮) (可选配) Tire type (front wheel/rear wheel)(Optional)	/	12.4-24/16.9-34	12.4-24/16.9-34
工作装置液压油泵型号 Model of hydraulic oil pump for working device	/	BTB320	BTB320
液压输出组数 (可选配) Number of hydraulic output groups (optional)	组/group	2/3	2/3
动力输出轴标准转速 Standard speed of power output shaft	r/min	540/760	540/760

- 后轮可调，满足不同农机需求，多种轮胎规格可选配，满足各种作业；
- 加强型免维护前桥，质量可靠，密封性好，转弯半径小；
- 液压转向，豪华减震座椅前后可调、驾驶舒适；
- 时尚流线型外观，驾驶室、机罩电泳烤漆，延长外观使用寿命；

The rear wheels are adjustable to meet the needs of different agricultural machinery. A variety of tire sizes are available for selection to meet various operations.
Reinforced maintenance-free front axle, reliable quality, good sealing and small turning radius;
Hydraulic steering, luxurious shock-absorbing seat adjustable front and rear, comfortable driving;
Fashionable streamlined appearance, cab and hood are electrophoretic painted to extend the service life of the appearance;



便携式后操纵机构
Portable Rear Manipulator



独立液压供油
Independent hydraulic oil supply



加强型护板
Reinforced guards



加强型专利驱动轴
Reinforced patented drive shaft



空调前出风口
Air conditioning front air vents



豪华驾驶室
Deluxe cab



- 后轮可调，全密封轮辋，满足不同农机需求，多种轮胎规格可选配，满足各种作业；
- 加强型免维护前桥，质量可靠，密封性好，转弯半径小；
- 液压转向，格拉默减震座椅前后可调、驾驶舒适；
- 时尚流线型外观，驾驶室、机罩电泳烤漆，延长外观使用寿命；

Adjustable rear wheels, fully sealed rims to meet the needs of different agricultural machines, a variety of tire specifications are optional to meet a variety of operations;
Reinforced maintenance-free front axle, reliable quality, good sealing, small turning radius;
Hydraulic steering, Grammer shock-absorbing seat adjustable front and rear, comfortable driving;
Stylish streamline appearance, cab, hood electrophoresis baking paint, prolong the service life of the appearance;



液压副油箱
Hydraulic auxiliary fuel tank



加强型专利底盘
Reinforced patent chassis



电控提升
Electric control lifting



750L超大油箱
750L large fuel tank



豪华驾驶室
Deluxe cab



180-210马力系列-轮式拖拉机

180-210 HP Series-Wheeled Tractor

技术特点/ Technical features

- 1、动力优越，匹配国内名牌电控四缸发动机，动力性能优越、节能环保，经济高效、作业高效。
 - 2、变速箱24+8/24+24换挡，前进、后退可快速切换：档位速度匹配多，可根据不同农具、不同土壤选择最佳的作业速度。
 - 3、先进底盘制造技术，TD2S底盘带自增力装置，加大半轴，谷禾加大前桥，铁流M8进口离合器片，性能安全可靠整机作业可靠性大幅度提升。
 - 4、豪华驾驶室，空调暖风、7寸带倒影仪表，多媒体影像，加强型锻打悬挂系统。
 - 5、采用独立的液压供油系统，增加液压副油箱，580F多路阀，液压输出4路及多路液压输出，满足多样化机具作业。
 - 6、液压离合助力，操纵力小于150N，较同类产品操纵力降低25%，安全可靠。
 - 7、底盘采用强制散热系统，传动系工作可靠性更高。
 - 8、750L大容量航空工程塑料油箱，持续作业时间长，重负荷深松作业12小时连续工作避免频繁加油。
 - 9、转弯半径≤4.9m，操作灵活，节省地头转弯时间，增加工作效率。
- 1、 Superior power, matched with domestic famous brand electronically controlled four 6-cylinder engine, superior power performance, energy saving and environmental protection, economic and efficient, efficient operation.
 - 2、 Transmission 24+8/24+24 gear shift, forward, backward can be quickly switched: gear speed matching more, according to different farm equipment, different soil to choose the best operating speed.
 - 3、 Advanced chassis manufacturing technology, TD2S chassis with self-boosting device, increased half-axle, GH increased front axle, Iron flow M8 imported clutch plate, safe and reliable performance of the whole machine operation Reliability is greatly improved.
 - 4、 Deluxe cab, air conditioning and warm air, 7-inch instrument with reflection, multimedia image, strengthened forged suspension system.
 - 5、 Independent hydraulic oil supply system, increase the hydraulic sub-tank, 580F multi-way valve, hydraulic output 4-way and multi-way hydraulic output, to meet the diversified implements work.
 - 6、 Hydraulic clutch booster, maneuvering force is less than 150N, 25% lower than similar products maneuvering force, safe and reliable.
 - 7、 The chassis adopts forced heat dissipation system, which makes the driveline more reliable.
 - 8、 750L large-capacity aviation engineering plastic fuel tank, long continuous operation time, heavy load deep pine operation 12 hours of continuous work to avoid frequent refueling.
 - 9、 turning radius ≤ 4.9m, flexible operation, save the ground turning time, increase work efficiency.

机 型/ models		1804-S	2104-S
整机驱动型式 Drive type	/	四驱/ Four-wheel drive	四驱/ Four-wheel drive
整机外部尺寸(长*宽*高及部位) Overall dimensions of the whole machine (length * width * height and position)	mm	5480*2240*3130 (警示灯顶部)(Warning light top)	5480*2240*3130 (警示灯顶部)(Warning light top)
轴距或履带接地长 Wheelbase or track grounding length	mm	2770	2770
轮距(前轮/后轮)或轨距 Track (front/rear wheels) or gauge	mm	1880/1760	1880/1760
挡位数 (前进/倒退) Number of gears (forward/backward)	/	16+16/24+8/24+24	16+16/24+8/24+24
发动机厂家 Engine manufacturer	/	上柴新动力 Shangchai new power	上柴新动力 Shangchai new power
发动机型号 Engine model	/	SC7H200G4(国四/Guosi)	SC7H230G4(国四/Guosi)
发动机标定功率 Engine calibration power	kw	132.5	155
轮胎型号(前轮/后轮) (可选配) Tire type (front wheel/rear wheel)(Optional)	/	14.9-28/18.4-38	14.9-28/18.4-38
工作装置液压油泵型号 Model of hydraulic oil pump for working device	/	CBT-G32/310	CBT-G32/310
液压输出组数 (可选配) Number of hydraulic output groups (optional)	组/group	4	4
动力输出轴标准转速 Standard speed of power output shaft	r/min	760/850	760/850

220-260马力系列-轮式拖拉机

220-260 HP Series-Wheeled Tractor

技术特点/ Technical features

- 后轮可调，全密封轮辋，满足不同农机需求，多种轮胎规格可选配，满足各种作业；
- 加强型免维护前桥，质量可靠，密封性好，转弯半径小；
- 液压转向，格拉默减震座椅前后可调、驾驶舒适；
- 时尚流线型外观，驾驶室、机罩电泳烤漆，延长外观使用寿命；

Adjustable rear wheels, fully sealed rims to meet the needs of different agricultural machines, a variety of tire specifications are optional to meet a variety of operations;
Reinforced maintenance-free front axle, reliable quality, good sealing, small turning radius;
Hydraulic steering, Grammer shock-absorbing seat adjustable front and rear, comfortable driving;
Stylish streamline appearance, cab, hood electrophoresis baking paint, prolong the service life of the appearance;

机 型/ models		2204-S	2404-S	2604-S
整机驱动型式 Whole machine drive type	/	四驱/ Four-wheel drive	四驱/ Four-wheel drive	四驱/ Four-wheel drive
整机外形尺寸(长*宽*高及部位) Overall dimensions of the whole machine (length * width * height and position)	mm	5600*2780*3380 (空滤器顶部/Air filter top)	5600*2780*3380 (空滤器顶部/Air filter top)	5600*2780*3380 (空滤器顶部/Air filter top)
轴距或履带接地长 Wheelbase or track grounding length	mm	2985	2985	2985
轮距(前轮/后轮)或轨距 Track (front/rear wheels) or gauge	mm	2000/1900	2000/1900	2000/1900
挡位数 (前进/倒退) Number of gears (forward/backward)	/	32+32	32+32	32+32
发动机厂家 Engine manufacturer	/	上柴新动力 Shangchai New Power	上柴新动力 Shangchai New Power	上柴新动力 Shangchai New Power
发动机型号 Engine model	/	SC7H240G4 (国四/national four-wheeler)	SC7H260G4 (国四/national four-wheeler)	SC7H290G4 (国四/national four-wheeler)
发动机标定功率 Engine calibration power	kw	162	177	191.5
轮胎型号(前轮/后轮) (可选配) Tire type (front wheel/rear wheel)(Optional)	/	540/65R30/650/65R42	540/65R30/650/65R42	540/65R30/650/65R42
工作装置液压油泵型号 Model of hydraulic oil pump for working device	/	CBT-G36/310	CBT-G36/310	CBT-G36/310
液压输出组数 (可选配) Number of hydraulic output groups (optional)	组/group	4	4	4
动力输出轴标准转速 Standard speed of power output shaft	r/min	760/850	760/850	760/850

- 1、动力优越，匹配国内名牌电控四6缸发动机，动力性能优越、节能环保，经济高效作业高效。
- 2、变速箱32+32换挡，前进、后退可快速切换：档位速度匹配多，可根据不同农具、不同土壤选择最佳的作业速度。
- 3、先进底盘制造技术，TS底盘带自增力装置，加大半轴，谷禾加大前桥，铁流M8进口离合器片，性能安全可靠整机作业可靠性大幅度提升。
- 4、豪华驾驶室，空调暖风、7寸带倒影仪表，多媒体影像选配，加大提升器加强型锻打悬挂系统。
- 5、采用独立的液压供油系统，增加液压副油箱，580F多路阀，液压输出4路及多路液压输出，满足多样化机具作业。
- 6、液压离合助力，操纵力小于150N，较同类产品操纵力降低25%，安全可靠。
- 7、底盘采用强制散热系统，传动系工作可靠性更高。
- 8、780L大容量航空工程塑料油箱，持续作业时间长，重负荷深松作业12小时连续工作，避免频繁加油。
- 9、转弯半径≤4.9m，操作灵活，节省地头转弯时间，增加工作效率。

- 1、Superior power, matched with domestic famous brand electronically controlled four 6-cylinder engine, superior power performance, energy saving and environmental protection, economic and efficient operation efficiency.
- 2、Transmission 32+32 gear shift, forward, backward can be quickly switched: gear speed matching, according to different farm equipment, different soil to choose the best operating speed.
- 3、Advanced chassis manufacturing technology, TS chassis with self-reinforcing device, increased half-axle, Valley Harvest increase the front axle, Iron flow M8 imported clutch plate, safe and reliable performance of the whole machine operation reliability greatly improved.
- 4、Deluxe cab, air-conditioning and warm air, 7-inch instrumentation with reflection, multimedia video options, increase the lifter to strengthen the forged suspension system.
- 5、the use of independent hydraulic oil supply system, increase the hydraulic sub-tank, 580F multi-way valve, hydraulic output 4-way and multi-way hydraulic output, to meet the diversified implements work.
- 6、Hydraulic clutch booster, maneuvering force is less than 150N, 25% lower than similar products maneuvering force, safe and reliable.
- 7、The chassis adopts forced heat dissipation system, which makes the driveline more reliable.
- 8、780L large-capacity aviation engineering plastic fuel tank, long continuous operation time, heavy load deep pine operation 12 hours of continuous work, to avoid frequent refueling.
- 9、turning radius ≤ 4.9m, flexible operation, save the ground turning time, increase work efficiency.



格拉默座椅
Grammer seats



多种轮胎规格可选配
Various tire sizes available



- 后轮可调，满足不同农机需求，多种轮胎规格可选配，满足各种作业；
- 加强型免维护前桥，质量可靠，密封性好，转弯半径小；
- 液压转向，豪华减震座椅前后可调、驾驶舒适；
- 时尚流线型外观，驾驶室、机罩电泳烤漆，延长外观使用寿命；

Rear wheels are adjustable to meet the needs of different agricultural machines, and a variety of tire specifications are optional to meet a variety of operations;
 Reinforced maintenance-free front axle, reliable quality, good sealing, small turning radius;
 Hydraulic steering, luxury shock-absorbing seats adjustable front and rear, comfortable driving;
 Fashionable streamline appearance, cab, hood electrophoresis baking paint, prolong the service life of appearance;

机 型/ models		804-B(G4)	904-B(G4)	1004-B(G4)
整机驱动型式 Whole machine drive type	/	四驱/ Four-wheel drive	四驱/ Four-wheel drive	四驱/ Four-wheel drive
整机外廓尺寸(长*宽*高及部位) Overall dimensions of the whole machine (length * width * height and position)	mm	4000*1850*2650 (安全架/Safety frame) 3645*1780*2700 (驾驶室/cab)	4000*1850*2650 (安全架/Safety frame) 3645*1780*2700 (驾驶室/cab)	3645*1780*2700 (驾驶室/cab)
轴距或履带接地长 Wheelbase or track grounding length	mm	2050	2050	2050
轮距(前轮/后轮)或轨距 Track (front/rear wheels) or gauge	mm	1200-1450/1200-1700	1200-1450/1200-1700	1200-1450/1200-1700
挡位数 (前进/倒退) Number of gears (forward/backward)	/	12+12	12+12	12+12
发动机厂家 Engine manufacturer	/	云内增压 Intra-cloud pressurization	云内增压/玉柴 Intra-cloud pressurization/Yuchai	云内增压/玉柴 Intra-cloud pressurization/Yuchai
发动机型号 Engine model	/	YN38TDE4	YN38TBE4/YCF39110-T481	YN38CCF4/YCF39120-T481
发动机标定功率 Engine calibration power	kw	59	66.2	74/73.5
轮胎型号(前轮/后轮) (可选配) Tire type (front wheel/rear wheel)(Optional)	/	9.5-24/14.9-30	9.5-24/14.9-30	9.5-24/14.9-30
工作装置液压油泵型号 Model of hydraulic oil pump for working device	/	BTB320	BTB320	BTB320
液压输出组数 (可选配) Number of hydraulic output groups (optional)	组/group	2/3	2/3	2/3
动力输出轴标准转速 Standard speed of power output shaft	r/min	540/760	540/760	540/760



豪华驾驶室

Deluxe cab



电控液压提升

Electrically controlled hydraulic lifting

B系列-轮式拖拉机

B series-wheeled tractor

技术特点/ Technical features

- 1、动力优越，匹配国内玉柴、云内名牌电控四缸发动机，动力性能优越、节能环保，经济高效、作业高效。
- 2、变速箱12+12梭式换挡，前进、后退可快速切换：档位速度匹配多，可根据不同农具、不同土壤选择最佳的作业速度。
- 3、先进底盘制造技术，加大半轴，性能安全可靠。
- 4、豪华驾驶室，空调暖风、多媒体影像选配，独家配备180L超大型油箱加强型悬挂系统。
- 5、采用独立的液压供油系统，并选装双路及多路液压输出，满足多样化机具作业。
- 6、双作用离合器、换挡动力输出链接更方便。

- 1、Superior power, matched with domestic Yuchai, Yunnei famous brand electronically controlled four-cylinder engine, superior power performance, energy saving and environmental protection, economic and efficient, efficient operation.
- 2、Transmission 12+12 shuttle shift, forward, backward can be quickly switched: gear speed matching more, according to different farm equipment, different soil to choose the best operating speed.
- 3、Advanced chassis manufacturing technology, enlarged half-axle, safe and reliable performance.
- 4、Deluxe cab, air conditioning and warm air, multimedia image optional, exclusively equipped with 180L super large fuel tank reinforced suspension system.
- 5、Independent hydraulic oil supply system, and optional dual-channel and multi-channel hydraulic output, to meet the diversified equipment operations.
- 6、Double-acting clutch, shift power output link is more convenient.



TF加强型快速挂接

TF Reinforced Quick Hookup



加强型免维护前桥

Reinforced maintenance-free front axle



加强型护板

Reinforced guards

H系列-轮式拖拉机

H series-wheeled tractor

技术特点/ Technical features

- 1、动力优越，匹配国内名牌电控四缸发动机，可选配潍柴、全柴、云内4102发动机，动力性能优越、节能环保，经济高效、作业高效。
- 2、变速箱可选装8+8/8+2换挡，梭式换挡前进、后退可快速切换：档位速度匹配多，可根据不同农具、不同土壤选择最佳的作业速度。
- 3、先进底盘制造技术，加强型底盘，加大后桥及半轴系统，性能安全可靠。
- 4、可选装平地板、分体挡泥板、豪华驾驶室，空调暖风、倒车影像选配加强型悬挂系统。
- 5、采用独立的液压供油系统，并选装单路及双路液压输出，满足多样化机具作业。
- 6、可选装单作用或双作用离合器、换挡动力输出链接更方便

- 1、Superior power, matched with domestic famous brand electronically controlled four-cylinder engine, optional Weichai, Quanchai, Yunnei 4102 engine, superior power performance, energy saving and environmental protection, economic and efficient, efficient operation.
- 2、Transmission can be equipped with 8+8/8+2 gear shift, shuttle shift forward and backward can be quickly switched: gear speed matching, according to different agricultural tools, different soil to choose the best operating speed.
- 3、Advanced chassis manufacturing technology, reinforced chassis, enlarged rear axle and half-axle system, safe and reliable performance.
- 4、optional flat floor, split fenders, luxury cab, air conditioning, warm air, reversing video optional reinforced suspension system.
- 5、Independent hydraulic oil supply system, and optional single and dual hydraulic output, to meet the diversified equipment operations.
- 6、Optional single-acting or double-acting clutch, shift power output link is more convenient.

机 型/ models		504-H(G4)	604-H(G4)	704-H(G4)
整机驱动型式 Whole machine drive type	/	四驱/ Four-wheel drive	四驱/ Four-wheel drive	四驱/ Four-wheel drive
整机外廓尺寸(长*宽*高及部位) Overall dimensions of the whole machine (length * width * height and position)	mm	3645*1480*2180 (安全架/Safety frame) 3645*1480*2480 (驾驶室/cab)	3645*1480*2180 (安全架/Safety frame) 3645*1480*2480 (驾驶室/cab)	3645*1480*2180 (安全架/Safety frame) 3645*1480*2480 (驾驶室/cab)
轴距或履带接地长 Wheelbase or track grounding length	mm	1910	1920	1920
轮距(前轮/后轮)或轨距 Track (front/rear wheels) or gauge	mm	860-1400/960-1455	860-1400/960-1455	860-1400/960-1455
挡位数 (前进/倒退) Number of gears (forward/backward)	/	8+2/8+8	8+2/8+8	8+2/8+8
发动机厂家 Engine manufacturer	/	全柴/潍柴/云内4102/扬动/玉柴 Quanchai/Weichai/Yunnei 4102/ Yangdong/Yuchai	全柴/云内 Quanchai/Yunnei	全柴/云内 Quanchai/Yunnei
发动机型号 Engine model	/	V28-50V42、WP3.2G50E434 YN38NKF4	V30-65C42	V30-75C42
发动机标定功率 Engine calibration power	kw	36.8	44.5	51.5
轮胎型号(前轮/后轮) (可选配) Tire type (front wheel/rear wheel)(Optional)	/	7.5-16/11.2-28	7.5-16/11.2-28	7.5-16/11.2-28
工作装置液压油泵型号 Model of hydraulic oil pump for working device	/	BTB316	BTB316	BTB316
液压输出组数 (可选配) Number of hydraulic output groups (optional)	组/group	1/2	1/2	1/2
动力输出轴标准转速 Standard speed of power output shaft	r/min	540/720	540/720	540/720

- 后轮可调，满足不同农机需求，多种轮胎规格可选配，满足各种作业；
- 加强型前桥，质量可靠，密封性好，转弯半径小；
- 液压转向，豪华减震座椅前后可调、驾驶舒适；
- 时尚流线型外观，驾驶室、机罩电泳烤漆，延长外观使用寿命；

Rear wheels are adjustable to meet the needs of different agricultural machines, and a variety of tire specifications are optional to meet a variety of operations;
Reinforced front axle, reliable quality, good sealing, small turning radius;
Hydraulic steering, luxury shock-absorbing seats adjustable front and rear, comfortable driving;
Fashionable streamline appearance, cab, hood electrophoresis baking paint, prolong the service life of appearance;



加强前桥
Reinforced front axle



液压副油箱
Hydraulic sub-tank



加大专利底盘
Increase patent chassis



加大后桥、专利半轴
提升器
Enlarged rear axle
Patented half-axle lifters



豪华专利驾驶室
Deluxe Patented Cab



技术特点/ Technical features

- 1、动力优越，匹配国内名牌国四电控四缸发动机，玉柴，潍柴，东方红，扬动，云内动力性能优越、节能环保，经济高效作业高效。
- 2、变速箱12+12梭式换挡，前进、后退可快速切换：档位速度匹配多，可根据不同农具、不同土壤选择最佳的作业速度。
- 3、先进底盘制造技术，加大半轴，性能安全可靠。
- 4、豪华驾驶室，空调暖风、多媒体影像选配，新式油箱，可配备180L超大型双油箱，加强型悬挂系统。
- 5、采用独立的液压供油系统，并选装双路及多路液压输出，满足多样化机具作业。
- 6、双作用离合器、换挡动力输出链接更方便。

- 1、Superior power, matched with domestic famous brand national four electronically controlled four-cylinder engine, Yuchai, Weichai, Dongfanghong, Yangdang, Yunnei power superior performance, energy saving and environmental protection, economic and efficient operation.
- 2、Transmission 12+12 shuttle shift, forward and reverse can be quickly switched: gear speed matching, according to different agricultural tools, different soil to choose the best operating speed.
- 3、Advanced chassis manufacturing technology, enlarged half-axle, safe and reliable performance.
- 4、Deluxe cab, air-conditioning, warm air, multimedia video options, new fuel tank, can be equipped with 180L super large double fuel tank, strengthened suspension system.
- 5、Independent hydraulic oil supply system, and optional dual-channel and multi-channel hydraulic output, to meet the diversified equipment operations.
- 6、Double-acting clutch, shift power output link is more convenient.



豪华驾驶室
Deluxe cab



XB加大前配重
XB increased front weight



XB系列-轮式拖拉机

XB series-wheeled tractor

- 后轮可调，满足不同农机需求，多种轮胎规格可选配，满足各种作业；
- 加强型免维护前桥，质量可靠，密封性好，转弯半径小；
- 液压转向，豪华减震座椅前后可调、驾驶舒适；
- 时尚流线型外观，驾驶室、机罩电泳烤漆，延长外观使用寿命；

Rear wheels are adjustable to meet the needs of different agricultural machines, and a variety of tire specifications are optional to meet a variety of operations;
Reinforced maintenance-free front axle, reliable quality, good sealing, small turning radius;
Hydraulic steering, luxury shock-absorbing seats adjustable front and rear, comfortable driving;
Fashionable streamline appearance, cab, hood electrophoresis baking paint, prolong the service life of appearance;



免维护前桥
Maintenance-free front axle



专利底盘-大TB12+12
Patented chassis-large TB12+12



双加大油箱
Dual enlarged fuel tanks

机 型/models		504-B	604-B	704-B
整机驱动型式 Whole machine drive type	/	四驱/ Four-wheel drive	四驱/ Four-wheel drive	四驱/ Four-wheel drive
整机外廓尺寸(长*宽*高及部位) Overall dimensions of the whole machine (length * width * height and position)	mm	4150*1850*2750(〈安全架/Safety frame〉 4150*1850*2800 (驾驶室/cab)	4150*1850*2750(〈安全架/Safety frame〉 4150*1850*2800 (驾驶室/cab)	4150*1850*2750(〈安全架/Safety frame〉 4150*1850*2800 (驾驶室/cab)
轴距或履带接地长 Wheelbase or track grounding length	mm	2050	2050	2050
轮距(前轮/后轮)或轨距 Track (front/rear wheels) or gauge	mm	1200-1450/1200-1700	1200-1450/1200-1700	1200-1450/1200-1700
档位数 (前进/倒退) Number of gears (forward/backward)	/	12+12	12+12	12+12
发动机厂家 Engine manufacturer	/	云内4102/Yunnei 4102	云内4102/Yunnei 4102	云内4102/Yunnei 4102
发动机型号 Engine model	/	YN38NKF4	YN38TBE4	YN38NDE4/WP3.2G75E440 V33-75C42
发动机标定功率 Engine calibration power	kw	36.8	44.5	51.5
轮胎型号(前轮/后轮)(可选配) Tire type (front wheel/rear wheel)(Optional)	/	9.5-24/14.9-30	9.5-24/14.9-30	9.5-24/14.9-30
工作装置液压油泵型号 Model of hydraulic oil pump for working device	/	BTB316	BTB316	BTB316
液压输出组数 (可选配) Number of hydraulic output groups (optional)	组/group	2/3	2/3	2/3
动力输出轴标准转速 Standard speed of power output shaft	r/min	540/760	540/760	540/760



自动化流水线
Automated assembly line

工厂装车照片 / Factory loading photos

目前公司销售渠道遍布东三省、内蒙、西藏、新疆及中原地区和南方水田区域，性能满足各区域使用要求。

At present, the company's sales and service channels cover the three northeastern provinces, Inner Mongolia, Tibet, Xinjiang, the Central Plains and the southern paddy field areas, and the performance meets the use requirements of various regions.



PTO实验台
PTO Test Bench



液压提升实验台
Hydraulic Lifting Test Bench



磨合台
Running-in Bench

部分产品展示

Part of the product display

《中国拖拉机行业最具影响力十大民族创新标杆品牌》

《全国拖拉机行业十佳优质品牌》

《中国绿色环保产品》

《中国自主创新产品》

"TOP TEN MOST INFLUENTIAL NATIONAL INNOVATION BENCHMARK BRANDS IN CHINA'S TRACTOR INDUSTRY"

"TOP TEN QUALITY BRANDS IN THE NATIONAL TRACTOR INDUSTRY"

"CHINA'S GREEN AND ENVIRONMENTALLY FRIENDLY PRODUCTS"

"CHINA'S INDEPENDENTLY INNOVATIVE PRODUCTS"



金诺瓦服务

GoldNova service

金诺瓦服务，始终以客户需求为宗旨。旗下拥有多支训练有素、经验丰富的服务队。每至农忙时节，他们便深入田间地头，主动靠前服务。无论是技术指导，还是设备维修，都能在现场及时解决农民遇到的难题，以实际行动助力农业生产。

GoldNova Service always aims to customer needs. it has multiple well-trained and experienced service teams. Whenever the busy farming season comes, they go deep into the fields and take the initiative to serve in front.

Whether it is technical guidance or equipment maintenance, it can solve the problems encountered by farmers in a timely manner on site and help agricultural production with practical actions.



未来公司进一步提升内部管理、技术能力，加强“内部”建设，做好人才储备，为公司持续全面发展农业机械产品打好基础！！

In the future, the company to further enhance internal management, technical capabilities, strengthen the “internal” construction, do a good job of talent reserves, for the company to continue to fully develop agricultural machinery products to lay a good foundation!